CILIP PREMIER HIGH SECURITY SAFES



for the security conscious



CMI SAFE CO.

Shop 2-3/ 227 Main St, Osborne Park WA 6017 Telephone: (08) 9344 1962

Website: www.mscsafeco.com.au Email: msc@mscsafeco.com.au

ALL CMI SAFES COME WITH A FIVE YEAR WARRANTY, EXCLUDING FREIGHT AND TRAVELLING, WITH A 12 MONTH WARRANTY ON LOCKS.

CMI PREMIER T.D.R.: The design of the safes and materials used provide defence barriers resisting to:

- Oxy-Acetylene attack
- Drills and abrasive grinders
- Explosives and force
- Pneumatic and hydraulic tools

BODY: The body gives a minimum thickness of 80mm of high density refractory materials at all points. These materials are bonded between inner and outer walls of specially reinforced steel, becoming a complete monolith after pouring. The engagement of the door and body effectively result in a continuous cube of exceptional strength and security. DOOR: The door of the Premier safe has an overall thickness of 135mm, and the 55mm thick defensive slab section contains metals highly resistant to drills and abrasive grinders in addition to the high-strength poured barrier materials and other defences. The lockcase forms an integral part of the entire door structure, giving additional strength.

BOLTWORK: Heavy 32mm bolts provide 4 way locking into reinforced sections of the 2 sides, top and bottom of the safe body.

INSURANCE COVER: Insurance surveyors have suggested \$45,000 as a realistic rating of overnight holding of cash and valuables in an unsupported situation.

OPTIONAL: 115mm high lockable roll-out drawer can be provided to secure in the bottom of Premier safes at additional



MODEL PR3

ANCHORING: 2 x 20mm recessed holes are provided in all models for anchor mounting to floor.

LOCKING: One La-Gard 6 digit electronic combination lock which secures the heavy duty 4 way locking 32mm bolt work, further supported by two automatic glass relockers. Powered by 1 x 9v alkaline battery.

A high quality key lock can be fitted as an optional extra if required at an additional cost.

FINISH: CMI Premier safes are available in attractive enamel hammertone durable finishes to suit any office decor. Satin finish handles, locks and fascia panels complement the high quality appearance.

INTERNAL FITTINGS: All models come standard with two adjustable shelves.

FIRE RESISTANCE

The Premier safe has been designed to be fire resisting for one hour

MODEL	CODE	HEIGHT	WIDTH	DEPTH	WEIGHT kg	LITRES	LOCKING POINTS	PRICE
PR1	External Internal	660 mm 508 mm	560 mm 405 mm	560 mm 330 mm	372	68	8	\$
PR2	External Internal	770 mm 615 mm	615 mm 457 mm	660 mm 435 mm	500	122	8	\$
PR3	External Internal	920 mm 762 mm	615 mm 457 mm	660 mm 435 mm	568	152	8	\$
PR4	External Internal	1075 mm 910 mm	660 mm 510 mm	660 mm 435 mm	704	202	10	\$
PR5	External Internal	1075 mm 910 mm	765 mm 610 mm	850 mm 585 mm	926	327	10	\$
PR6	External Internal	1225 mm 1066 mm	765 mm 610 mm	850 mm 585 mm	1026	381	10	\$
PR7	External Internal	1375 mm 1220 mm	765 mm 610 mm	850 mm 585 mm	1128	435	12	\$
PR8	External Internal	1525 mm 1370 mm	765 mm 610 mm	850 mm 585 mm	1230	489	12	\$
PR9	External Internal	1675 mm 1520 mm	765 mm 610 mm	850 mm 585 mm	1345	542	12	\$
PR10	External Internal	1825 mm 1675 mm	765 mm 610 mm	850 mm 585 mm	1464	595	12	\$

(IMPORTANT: PLEASE ALLOW 55MM PROJECTION FOR DOOR FURNITURE ON DEPTH MEASUREMENT)

CMI Safe Co. reserve the right to alter specifications without notice or obligation.

To deliver and install level access metro



AVAILABLE FROM

