



PREMIER

HIGH SECURITY SAFES



for the security conscious



CMI SAFE CO.

Head Office: 244 West Street Carlton NSW 2218

Telephone: (02) 9547 1488 Fax: (02) 9547 2104

Website: <http://www.cmisafe.com.au> Email: sales@cmisafe.com.au

ALL CMI SAFES COME WITH A FIVE YEAR WARRANTY, EXCLUDING FREIGHT AND TRAVELLING, WITH A 12 MONTH WARRANTY ON LOCKS.

CMI PREMIER T.D.R.: The design of the safes and materials used provide defence barriers resisting to:

- **Oxy-Acetylene attack**
- **Drills and abrasive grinders**
- **Explosives and force**
- **Pneumatic and hydraulic tools**


BODY: The body gives a minimum thickness of 80mm of high density refractory materials at all points. These materials are bonded between inner and outer walls of specially reinforced steel, becoming a complete monolith after pouring. The engagement of the door and body effectively result in a continuous cube of exceptional strength and security.

DOOR: The door of the Premier safe has an overall thickness of 135mm, and the 55mm thick defensive slab section contains metals highly resistant to drills and abrasive grinders in addition to the high-strength poured barrier materials and other defences. The lockcase forms an integral part of the entire door structure, giving additional strength.

BOLTWORK: Heavy 32mm bolts provide 4 way locking into reinforced sections of the 2 sides, top and bottom of the safe body.

INSURANCE COVER: Insurance surveyors have suggested **\$45,000** as a realistic rating of overnight holding of cash and valuables in an unsupported situation.

OPTIONAL: 115mm high lockable roll-out drawer can be provided to secure in the bottom of Premier safes at additional



MODEL PR3

ANCHORING: 2 x 20mm recessed holes are provided in all models for anchor mounting to floor.

LOCKING: One La-Gard 6 digit electronic combination lock which secures the heavy duty 4 way locking 32mm bolt work, further supported by two automatic glass relockers. Powered by 1 x 9v alkaline battery.

A high quality key lock can be fitted as an optional extra if required at an additional cost.

FINISH: CMI Premier safes are available in attractive enamel hammertone durable finishes to suit any office decor. Satin finish handles, locks and fascia panels complement the high quality appearance.

INTERNAL FITTINGS: All models come standard with two adjustable shelves.

FIRE RESISTANCE
The Premier safe has been designed to be fire resisting for one hour

MODEL	CODE	HEIGHT	WIDTH	DEPTH	WEIGHT kg	LITRES	LOCKING POINTS	PRICE
PR1	External	660 mm	560 mm	560 mm	372	68	8	\$
	Internal	508 mm	405 mm	330 mm				
PR2	External	770 mm	615 mm	660 mm	500	122	8	\$
	Internal	615 mm	457 mm	435 mm				
PR3	External	920 mm	615 mm	660 mm	568	152	8	\$
	Internal	762 mm	457 mm	435 mm				
PR4	External	1075 mm	660 mm	660 mm	704	202	10	\$
	Internal	910 mm	510 mm	435 mm				
PR5	External	1075 mm	765 mm	850 mm	926	327	10	\$
	Internal	910 mm	610 mm	585 mm				
PR6	External	1225 mm	765 mm	850 mm	1026	381	10	\$
	Internal	1066 mm	610 mm	585 mm				
PR7	External	1375 mm	765 mm	850 mm	1128	435	12	\$
	Internal	1220 mm	610 mm	585 mm				
PR8	External	1525 mm	765 mm	850 mm	1230	489	12	\$
	Internal	1370 mm	610 mm	585 mm				
PR9	External	1675 mm	765 mm	850 mm	1345	542	12	\$
	Internal	1520 mm	610 mm	585 mm				
PR10	External	1825 mm	765 mm	850 mm	1464	595	12	\$
	Internal	1675 mm	610 mm	585 mm				

(IMPORTANT: PLEASE ALLOW 55MM PROJECTION FOR DOOR FURNITURE ON DEPTH MEASUREMENT)

CMI Safe Co. reserve the right to alter specifications without notice or obligation.

To deliver and install level access metro

AVAILABLE FROM



CD BBF KB 16/11/05

MADE IN AUSTRALIA